

Voice Phone

KSV Series



Part Number Description

KSV - IC **1** (without Speaker)

1 Voice Type 04 : 4 Channel Voice 08 : 8 Channel Voice

KSV - **1** **2** **3**

1 Size S : □ 48mm L : □ 72mm

2 Color S : Silver K : Black

3 Voice Type 04 : 4 Channel Voice 08 : 8 Channel Voice




General Specification

Model	KSV-IC04/08	KSV-L	KSV-S
Power Consumption	Max. Approx. 15W	5W	5W
Maximum Rated Output	Approx. 10W, 90dB/1m	2W 80 ~ 90dB(Phon) / 1m	2W 80 ~ 85dB(Phon) / 1m
Supply Voltage	12/24VDC		
Recordable Memory	64sec (16MHz) / 128sec (8MHz)		
Ambient Temperature	-20 ~ 55 °C (with no icing)		
Insulation Resistance	100MΩ 500VDC		
Dielectric Strength	1,000VAC 1 Minute		
Vibration Resistance	10 ~ 50Hz wavelength 1.5mm		
Tightening Torque	0.5N·m (5.10kgf·cm)		

Note) In case of S Type speaker, life may be shortened when energized continuously for a long time.

☞ The specification and material of the product can be changed without notice for better quality.
Speaker (IC04/08) : 8 ohm lower than 10W

Product Selection

Description	Front Part (Speaker) Size	Part Number	
		Silver	Black
 Digital Signal Voice Phone	Large	KSV-LS	KSV-LK
 Digital Signal Voice Phone	Small	KSV-SS	KSV-SK
 4-Channel Voice Phone Chip	-	-	KSV-IC04
8-Channel Voice Phone Chip	-	-	KSV-IC08